

IN THE CLAIMS:

Please substitute amended claims 1, 2, 9, 12 through 14, and 18 through 20 as follows for the pending claims with the same number:

Sub
b2
A2

1. (AMENDED) A trailer hitch cover assembly comprising:
a main body adapted to be disposed over a hitch tube and adapted to allow insertion of a hitch into the hitch tube;
an insulating member adapted to be disposed over the hitch tube and between said main body and the hitch tube; and
a cover plate hingedly connected to said main body and being movable between a closed position and an open position.

2. (AMENDED) A trailer hitch cover assembly comprising:
a main body operatively connected to a hitch tube and adapted to allow insertion of a hitch into the hitch tube;
a cover plate hingedly connected to said main body and being movable between a closed position and an open position; and
wherein said main body includes at least one deflectable tab to retain said main body on the hitch tube.

A3

9. (AMENDED) A trailer hitch cover assembly comprising:
a main body operatively connected to a hitch tube and adapted to allow insertion of a hitch into the hitch tube;
an insulating member disposed between said main body and the hitch tube;

*b2
cont*
a cover plate hingedly connected to said main body and being movable between a closed position and an open position;

*A3
cont*
wherein said main body includes a plurality of apertures extending therethrough;

and

wherein said insulating member includes a plurality of pins extending outwardly and through said apertures in said main body to connect said insulating member to said main body.

do not connect insulating member to main body

A4
12. (AMENDED) A trailer hitch cover assembly for a motor vehicle comprising:

a main body adapted to be disposed over a hitch tube and having a front face with an opening adapted to allow passage of a hitch into an open end of the hitch tube;

an insulating member disposed within and operatively connected to said main body; and

a movable cover plate hingedly connected to said main body to be moved between a first position and a second position.

13. (AMENDED) A trailer hitch cover assembly comprising:
a main body for connection to a hitch tube and having a front face with an opening adapted to allow passage of a hitch into an open end of the hitch tube;

an insulating member disposed within and operatively connected to said main body;

a movable cover plate hingedly connected to said main body to be moved between a first position and a second position; and

b2
cont
AY
cont

wherein said main body includes opposed side walls extending from said front face with at least one deflectable tab to retain said main body on the hitch tube.

14. (AMENDED) A trailer hitch cover assembly as set forth in claim 12 wherein each of said sidewalls include^s at least one aperture extending therethrough adapted to allow passage of a lock pin.

AS

18. (AMENDED) A trailer hitch cover assembly comprising:
 a main body for connection to a hitch tube and having a front face with an opening adapted to allow passage of a hitch into an open end of the hitch tube;
 a movable cover plate hingedly connected to said main body to be moved between a first position and a second position;
 wherein said main body includes a plurality of apertures extending through said sidewalls.

19. (AMENDED) A trailer hitch cover assembly comprising:
 a main body for connection to a hitch tube and having a front face with an opening adapted to allow passage of a hitch into an open end of the hitch tube;
 an insulating member disposed within and operatively connected to said main body;
 a movable cover plate hingedly connected to said main body to be moved between a first position and a second position;
 wherein said main body includes a plurality of apertures extending through said sidewalls; and

b2
cont

wherein said insulating member includes a plurality of pins extending outwardly and through said apertures to connect said insulating member to said main body.

20. (AMENDED) A hitch cover assembly comprising:

a hitch tube having a first opening adapted to receive a hitch;

A5
cont

a main body disposed over said hitch tube and having a front face with a second opening to allow passage of the hitch into said first opening and in said hitch tube;

an insulating member disposed within and operatively connected to said main body; and

a movable cover plate hingedly connected to said main body to be moved between a first position to close said first opening and a second position to open said first opening.
